

# 2D WIRELESS BARCODE SCANNER

# DCCode®

# DC7122



NEW ABS DESIGN, COMFORTABLE TO USE



24G WIRELESS. UPTO 100M RANGE



STORE UP TO 100,000 BARCODES



32 BITS CPU – SUPER DECODING ABILITY.

## TECHNICAL SPECIFICATIONS

Scan Type	Area Imager
Lighting Aimer	CMOS 640 x 480
Storage	100,000 Barcodes
Scanning Speed	500 per second
Scan Angle	Rotation 30° / Incline ±55° / Decline ±60°
Resolution	4 mil
CPU	ARM 32 bit Cortex
Battery	2500 mAh Li-ion
Transmission Range	Indoor max 50 meters   Outdoor max 100 meters
Interface	USB + Dongle
Prompt Mode	Buzzer, LED
Decoding Capability	UPC-A, UPC-E, Code128, EAN-13, EAN-8, ISBN, Code 93, UCC/EAN-128, GS1 Code39, Code 39FullASCII, Codabar, Interleaved 2 of 5, Databar, MSI, Code11, ISBN, ISSN, China post, etc 2D: QR code, PDF 417, Data Matrix, Aztec, Maxicode etc
Electric Voltage	5V DC
Current Ambient	Work 86mA, Standby 42mA, Starting 130mA
Light Immunity	0-110,000 Lux
<b>Mechanical Parameters</b>	
Dimensions	170mm x 92mm x 55mm
Weight	176g
<b>Environmental Parameters</b>	
Working Temperature	-0°C ~ 50°C
Storage Temperature	-30°C ~ 70°C
Humidity	5% to 95% Relative Humidity, Non Condensing
Drop Test	2m
<b>Warranty</b>	
24 Months against any manufacturing defect	

## APPLICATIONS



RETAIL



LOGISTICS



HOSPITAL



JEWELRY



WAREHOUSE



DCCode®

hello@dcodeinternational.in



www.dcodeinternational.in

DELHI NCR

MUMBAI

AHEMDABAD

SURAT

TIRUPUR

CHENNAI

LUDHIANA

PUNE

KOLKATA

COIMBATORE

GUWAHATI

